



FR-500WK

FR-500WT WIRELESS TRANSMITTER

- Ultra High Frequency range: 566.25 - 589.75 MHz
- 64 channels selections. (4 groups x 16 channels)
- Wide frequency response: 40Hz-18kHz
- Built-in microphone
- 1/8" (3.5 mm) mic jack
- 1/8" (3.5 mm) mono line in

Includes:

- omni lavalier microphone
- microphone clip
- windscreen

FR-500WR WIRELESS RECEIVER

- Ultra High Frequency range: 566.25 - 589.75 MHz
- 64 channel selections. (4 groups x 16 channels)
- Wide frequency response: 40Hz-18kHz
- Built-in speaker
- 1/8" (3.5 mm) headphone jack
- 1/8" (3.5 mm) line out

Includes:

- Hot Shoe Mount
- 1/8" to 1/8" cable
- 1/8" to XLR male
- 1/4" adapter

SPECIFICATIONS

Model	FR-500WT/FR-500WR
Frequency Range	566.25 - 589.75 MHz
Frequency Response	40 Hz-18 kHz
Operating Range	Up to 280m
Channels	64 (4 groups of 16 channels)
Controls	Power On/Off, Channel Selection, Volume Control, Group Selection, Boost
Battery	Each unit requires 2x AA (not included)
Battery Life	10 hours typical
Dimensions (each)	62mm(W) x 20mm(D) x 97mm(H)

