

7-channel 2U install mixer - 3 zones

DAP

EAN: 8717748316141



The DAP IMIX-7.1 is a 7-channel installation mixer with 3 master outputs. This allows you to make a good mix between the different inputs and the master volume. You also have the option to adjust the EQ settings for each output. In total you can connect two dynamic microphones and five audio devices, with the microphone inputs equipped with a 3-band EQ control and a talkover function that works on both channels.

The gain settings for each input are located on the back. This prevents clipping by non-technical users. On the front there is a direct input for 2 microphones, 1 line source or a telephone/MP3 device with a special impedance switch.

Special features:

- 19"/2U installation mixer
- Suitable for restaurants, retail, public places and nightlife
- 2x mic input with volume and EQ control
- 5x line input with individual volume (faders) and gain control
- 3 master outputs with volume control & EQ settings

Specifications:

Inputs

Mono Inputs	2
Mono Input Connector	3-pin XLR / TRS balanced 6.3 mm
Stereo Inputs	10
Stereo Input Connector	RCA
Phono Audio Inputs	2
Phono Audio Input Connector	RCA
Auxiliary Inputs	1
Auxiliary Input Connector	RCA / TRS balanced 3.5 mm

Outputs

Main Outputs	3
Main Output Connector	3-pin XLR / RCA
Headphone Output	1
Headphone Output Connector	TS unbalanced 6.3 mm
Record Output	1
Record Output Connector	RCA

Extension Module

Media Player	No
--------------	----

Digital Playback

Audio Interface	No
-----------------	----

Audio Specifications

THD Level %	< 0.05 %
Signal-to-noise Ratio	> 100 dB
Frequency Response Minimum	20 Hz
Frequency Response Maximum	20000 Hz

Sound Editing

Microphone Input Equalizer Gain Range	12 dB
Parametric Microphone Equalizer	3 Bands
Microphone Input Fixed Frequencies	80, 1.000, 12.000 Hz
Parametric Main Equalizer	3 Bands
Main Output Equalizer Gain Range	12 dB
Main Output Fixed Frequencies	80, 1.000, 12.000 Hz

Wireless Specifications

BT	No
----	----

Product Properties

LED Indicators	Channel select / Clip / Output level / Signal
----------------	---

Electrical Specifications and Connections

Power Supply	220-240 V AC 50 Hz (Power adapter)
Output voltage	18 V AC
Power Consumption	16.5 W
Power Connector In	Low Voltage AC plug

Mechanical Specifications

Fader Length	60 mm
Height (mm)	89 mm
Width (mm)	483 mm
Depth (mm)	89 mm
Flightcase Size	19"
Rack Units	2 U
Housing	Metal
Colour	Black
Weight	2.8 kg
IP Rating	IP20 (indoor use only)

Included Items

Included Accessories	Adapter
----------------------	---------

Downloads:

Manual

[D2350_MANUAL_GB_V1.pdf](#)

Declaration

[D2350_DoC_2026.pdf](#)