



The DAP SDI-202 is a multifunctional DI-Box. It can be used to amplify a signal or create a balanced output. Activating the ground lift provides an even frequency response to any input signal with the benefit of canceling out interference, hums and buzzes. You can switch between instrument and speaker mode.

Instrument mode can be used to connect an instrument with high output impedances, such as an electric guitar or acoustic guitar with a piezo-ceramic pickup. In addition, you can connect electrical devices with an unbalanced output, such as a keyboard or DJ mixer without balanced outputs.

Speaker mode allows you to balance the output of a guitar amp to create a clean, low-level signal, allowing your signal to be driven through long cables with no problem.

Special features:

- RCA/2x 6.3 mm TS Jack in, 2x balanced XLR out
- Prevents ground loops, hum and buzz
- Road proof housing with rubber feet
- 9 V power supply or 18-48 V phantom power
- Ground lift
- Instrument & speaker inputs

Specifications:

Inputs

Mono Inputs	2
Mono Input Connector	RCA / TS unbalanced 6.3 mm
Balanced Mono Input Nominal Level	9 dBu
Balanced Mono Input Maximum Level	39 dBu
Mono Input Impedance	47 Ω

Outputs

Main Outputs	2
Main Output Connector	3-pin XLR
Main Output Impedance	600 Ω

Audio Specifications

THD Level %	< 0.005 %
Signal-to-noise Ratio	> 105 dB
Frequency Response Minimum	10 Hz
Frequency Response Maximum	40000 Hz
Phantom Power	18 V / 24 V / 48 V

Battery

Battery Type	9 V block PP3
--------------	---------------

Mechanical Specifications

Height (mm)	53 mm
Width (mm)	158 mm
Length (mm)	135 mm
Housing	Metal
Weight	0.7 kg
IP Rating	IP20 (indoor use only)
Colour	Black

Product Properties

LED Indicators	Ground lift / Inst. - Speaker / Operation mode / Power
----------------	--

Downloads:

Manual

[D1947_MANUAL_GB_V1.pdf](#)