

D1904

DAP AS-8

*8-channel XLR/jack 3-pin audio
splitter/mixer*

DAP

EAN: 8717748033383



The DAP AS-8 can be used for multiple purposes. The intelligent design makes it easy to switch between a controllable audio mixer with multiple inputs, to a signal splitter with multiple controllable outputs. This makes the AS-8 a multifunctional solution for your own monitor mix, multi-zone system, conference application and more.

Special features:

- 2x Jack and 6x XLR in/out
- Switchable splitter/mixer function
- Large headroom

Specifications:

Inputs

Mono Inputs	8
Mono Input Connector	3-pin XLR / TRS balanced 6.3 mm
Balanced Mono Input Maximum Level	21 dBu
Mono Input Impedance	50 Ω

Outputs

Main Outputs	8
Main Output Connector	3-pin XLR / TRS balanced 6.3 mm
Main Output Impedance	60 Ω

Audio Specifications

THD Level %	< 0.002 %
Signal-to-noise Ratio	> 95 dB
Frequency Response Minimum	5 Hz
Frequency Response Maximum	40 Hz

Electrical Specifications and Connections

Power Supply	240 V AC 50/60 Hz
Power Consumption	11.2 W
Fuse	0.315 A
Power Connector In	IEC

Mechanical Specifications

Height (mm)	44 mm
Width (mm)	483 mm
Length (mm)	195 mm
Flightcase Size	19"
Rack Units	1 U
Weight	2.7 kg
IP Rating	IP20 (indoor use only)
Housing	Metal
Colour	Black

Product Properties

LED Indicators	Input level / Output level / Power
----------------	------------------------------------

Included Items

Included Cables	IEC cable
Included Accessories	Rubber feet

Downloads:

Manual

[D1904_MANUAL_GB_V1.pdf](#)