

ND76S



- Excellent all-around vocal performance: crisp, clear and balanced
- Large diaphragm dynamic capsule creates a rich and detailed frequency response
- Shock-mounted capsule minimizes handling noise
- Humbucking coil guards against line hum
- Memraflex grille resists denting



The Electro-Voice ND76S is a robust, high-performance dynamic cardioid vocal microphone. Designed for excellent all-around voice applications, the ND76S capsule is precisely tuned to deliver crisp, clear and balanced vocal presence, as well as superior isolation from sound on the stage. The ND76S dynamic capsule contains a large Mylar diaphragm which delivers a rich and detailed frequency response by combining its large surface area for tonal balance with its low-mass high-velocity material for exceptionally fast transient response. The ND76S features an innovative capsule shock-mount system consisting of a 4-point suspension around the circumference of the capsule combined with a tuned pneumatic pump at the capsule base, offering superior handling noise reduction to eliminate mechanical vibrations and noise in the mix. The ND76S capsule uses a humbucking coil that attenuates AC hum and electromagnetic interference. ND dynamic mics can be used with confidence near speaker cabinets and EMF generating equipment racks. The ND76S Memraflex grille is made of a durable tight-mesh grille wire that withstands extraordinarily-rough treatment. Your microphone remains protected and looking good gig-after-gig, year-after-year. For additional protection, the ND76S capsule contains a hydrophobic cloth membrane which prevents moisture and debris from reaching the diaphragm.

The ND76S near-silent on/off switch allows the user the convenience of turning on and off the mic as needed. The on/off switch can be locked into the on position by using a flat head screwdriver to rotate the set screw 90° either clockwise or counterclockwise.

Technical specifications


Element Type:	Dynamic neodymium magnet structure
Frequency Response, Close:	30 Hz – 17 kHz
Frequency Response, Far:	70 Hz – 17 kHz
Polar Pattern:	Cardioid
Sensitivity, Open Circuit Voltage @ 1 kHz:	2.4 mV/Pascal
Maximum SPL:	>140 dB
Polarity:	Pin 2 positive, reference to pin 3 with positive pressure on diaphragm
Impedance:	350 ohms balanced (low-z)
Microphone Connector:	3-pin, XLR-type
Finish:	Black polyurethane paint
Material:	Zinc die cast handle, Memraflex grille screen
Dimensions, Length:	7.2 in (182.5 mm)
Diameter:	2.0 in (50.5 mm)
Shank:	0.96 in (24.3 mm)

Net Weight: 11.2 oz (318 g)


Shipping Weight: 20.9 oz (573 g)

Accessories Included: (1) Gig bag, (1) stand clip, and (1) Euro thread adapter


Frequency Response:



Polar Response:



Dimensions:



Parts included

Qty.	Item
1	Microphone
1	Gig bag
1	Stand clip
1	Euro thread adapter
1	Engineering data sheet
1	Warranty and Product Documentation Information card

Ordering information

ND76S

Dynamic cardioid vocal microphone with on/off switch, black

Order number **ND76S**

NDVOCCLIP

Replacement stand adapter, black

Order number **NDVOCCLIP**

ND76GRILLE

Replacement end grille, black

Order number **ND76GRILLE**

NDVOCRING

Replacement transition ring between grille sections, silver

Order number **NDVOCRING**

Accessories

379-1

Foam windscreen/pop filter, black

Order number **379-1**

Represented by:

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Germany

www.electrovoice.com

Bosch Security Systems, Inc.
12000 Portland Avenue South
Burnsville MN 55337
USA