

EUROLITE LED Theatre COB 100 WW/CW

LED theatre spot with 2in1 CW/WW 100 W COB (chip-on-board) LED

Art. No.: 41602014

GTIN: 4026397685886



List price: 248.71 €

incl. 19% VAT.

Features:

- Variable color temperature 2500 K - 5700 K
- With a beam angle of 41°
- Very high color rendering index (CRI)
- Flicker-free
- Integrated show programs
- With double bracket
- Mains input and output for power linking up to 8 units
- Control via DMX; stand-alone; master/slave function; sound to light via microphone; CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
- For application areas such as: Stage; wedding/gala/events; Trade fair and shop fitting; restaurants, bars and hotels; video and photography; advertisement/Shop window
- Application possibility: Standing; suspended; on stand
- Can be operated in 2; 4; 5; 7 CH mode

Logistic

EAN / GTIN: 4026397685886

Weight: 3,11 kg

Length: 0.26 m

Width: 0.23 m

Height: 0.34 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	85 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (grey), mounting version

Fuse:	T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) 2in1 CW/WW
Flash rate:	0.5 - 23 Hz
DMX channels:	2; 4; 5; 7
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone; master/slave function; sound to light via microphone; CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
Fixtures available for:	Light' J; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	41°
Beam angle (1/2 peak):	41°
Beam angle (1/10 peak):	65°
Color temperature:	2500K - 5700K adjustable
Color rendering index (CRI):	95 Ra
Illuminance in Lux (lx):	Cold white (CW) 1m: 2573 lx, 3m: 296 lx, 6m: 90 lx Warm white (WW) 1m: 1413 lx, 3m: 176 lx, 6m: 53 lx All 1m: 3366 lx, 3m: 407 lx, 6m: 107 lx
Housing color:	Black matte
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Material:	Plastic; metal
Dimensions:	Width: 24.3 cm Depth: 31.1 cm Height: 32.0 cm
Weight:	2.75 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Diameter mounting holes:	1 x Ø11mm
Material:	Metal, 2.5 mm
Material:	Metal, 0.8 mm
Cable construction:	3 x 1.0 mm² H03VV-F
Cable length:	Approx. 1.2 m

Scope of delivery:

1 x spotlight
1 x power cord
1 x user manual