

FL743

DAP FL74 XLR M/F Mic/Line
Cable Neutrik XX series 3 m -
silver plated

3 m - silver plated

DAP

EAN: 8717748455529



Microphone/line cable constructed out of MC-226 double insulated cable and Neutrik NC3 mXX + NC3FXX cable connectors. 3-pin male and female cable connectors with Nickel housing and silver contacts. The next generation of the worldwide accepted standard of XLR cable connectors. The successor of the X series offers several new features which make it more reliable, easier to assemble and improves contact integrity as well cable strain relief.

Specifications:

Electrical Specifications and Connections

Impedance	110 Ω
Connector 1	XLR 3P
Connector 2	XLR 3P
Brand Connector 1	Neutrik
Cable Length	3 m
Pins	3
Conductor Resistance	90 Ω /km
Conductor Capacitance	60 pF/m
Capacity Inner Conduct. Shield/Inner Conduct.	78 pF/m
Outer Cable Diameter	6 mm
Outer Isolation Diameter	6 mm
Outer Isolation Type	PVC

Mechanical Specifications

Weight	0.212 kg
IP Rating	IP40
Material	PVC
Colour	Black
Contact Resistance	3 < m Ω

Product Properties

Contact Type	Silver plated
1st Shield	Conductive Plastic
2nd Shield	Oxygen Free Copper
Shield Resistance	25 Ω /km
Conductors	3

Thermal Specifications

Maximum Ambient Temperature	60°C
Minimum Ambient Temperature	-20°C

Downloads:

Declaration

[FL743_DC_2019.pdf](#)