

FLX0815
0

DAP FLX08 - DMX/AES-EBU
XLR/M 5P to XLR/F 5P 1.5 m

1.5 m

DAP

EAN: 8717748553775



This 110-Ohm DMX cable is designed for the optimal transmission of AES/EBU digital signals. It comes with hook-and-loop fastener and the latest DAP DMX connectors that can accommodate different colour rings.

Special features:

- 110-Ohm DMX cable
- Changeable colour rings
- Hook-and-loop fastener included

Specifications:

Electrical Specifications and Connections

Connector 1	XLR 5P
Connector 2	XLR 5P
Impedance	110 Ω
Cable Length	1.5 m
Pins	5
Conductor Resistance	80 Ω /km
Capacity Inner Conduct. Shield/Inner Conduct.	64 pF/m
Wire Connection	0.34 mm ²
Outer Cable Diameter	7.5 mm
Outer Isolation Diameter	7.5 mm
Outer Isolation Type	PVC

Mechanical Specifications

Weight	0.171 kg
IP Rating	IP20 (indoor use only)
Material	Copper
Colour	Black

Product Properties

Contact Type	Silver plated
1st Shield	Braided Tinned Copper
2nd Shield	Aluminium foil
Shield Resistance	30 Ω /km
Filler Material	Paper
Conductors	4

Thermal Specifications

Maximum Ambient Temperature	70°C
Minimum Ambient Temperature	-20°C

Product Accessories:

XXBL	Ring for X-type XLR Connector Blue
XXGR	Ring for X-type XLR Connector Green
XXOR	Ring for X-type XLR Connector Orange
XXRE	Ring for X-type XLR Connector Red
XXYE	Ring for X-type XLR Connector Yellow

Downloads:

Declaration

[FLX08150_DoC_2023.pdf](#)