

SKB CASES **rSeries 4714-10 Case**



The rSeries Mil-Standard cases have been designed to meet the most exacting military specifications. They are roto-molded of impact-resistant/UV stabilized LLDPE for strength and durability, featuring airtight and waterproof construction with solid stainless steel latches and hinges that will withstand the most demanding shipping conditions. Our rSeries cases come standard with an empty interior, and some models are available with: cubed foam, layered foam, padded dividers, and a pull handle with wheels.

Features

- Accepts the 1SKB-PDL or the 1SKB-PDL-C Combination TSA Padlock
- Waterproof and dust tight design (MIL-C-4150J)
- LLDPE Polyethylene impact resistant
- UV, solvents, corrosion, fungus resistant (MIL-STD 810H)
- Pressure relief / breather valves
- Resistant to impact damage (MIL-STD 810H)
- Stainless steel latches and hinges
- Waterproof and dust tight design (MIL-C-4150J)
- LLDPE Polyethylene impact resistant
- UV, solvents, corrosion, fungus resistant (MIL-STD 810H)
- Pressure relief / breather valves
- Resistant to impact damage (MIL-STD 810H)
- Stainless steel latches and hinges
- Waterproof and dust tight design (MIL-C-4150J)
- LLDPE Polyethylene impact resistant
- UV, solvents, corrosion, fungus resistant (MIL-STD-810F)
- Pressure relief / breather valves
- Resistant to impact damage (MIL-STD-810F)
- Stainless steel latches and hinges

Specification	Imperial	Metric
Exterior	Hard	
Built In Wheels or Casters	No	

Specification	Imperial	Metric
Interior Length	47.5 in	120.65 cm
Interior Width	14.38 in	36.53 cm
Interior Lid Depth	5 in	12.70 cm
Interior Base Depth	5.5 in	13.97 cm
Exterior Length	50.75 in	128.91 cm
Exterior Width	17.13 in	43.51 cm
Exterior Height	12.25 in	31.12 cm
Carton Length	52 in	132.08 cm
Carton Width	17.5 in	44.45 cm
Carton Height	13 in	33.02 cm
Product Weight	29.16 lb	13.23 kg
Shipping Weight	33.06 lb	15.00 kg
Max Temp	0 °F	-17.78 °C
Min Temp	0 °F	-17.78 °C