

Spark LINK XLR Technical Specification

CORE SPECIFICATIONS

FREQUENCY RESPONSE

20Hz ~ 20kHz

SAMPLE RATE / BIT DEPTH

48kHz / 24-bit

LATENCY

< 3ms

DYNAMIC RANGE

103.7 dB

POWER

MAIN INPUT POWER

DC 5V/1A (USB)

BATTERY TYPE

500mAh rechargeable lithium-ion battery

PLAY TIME

Up to 7 hours of continuous use

CHARGING TIME

2 hours

CONTROLS AND CONNECTIVITY

TOP PANEL CONTROLS & DISPLAYS

Power button

LED indicator

REAR PANEL

USB Type-C charging port

WIRELESS CONNECTIVITY

Positive Grid proprietary wireless audio (2.4GHz)

TRANSMISSION RANGE

Up to 70 feet line-of-sight (21 meters)

COMPATIBLE CHANNELS

4 channels

INCLUDED IN THE BOX

BOX CONTENTS

Spark LINK XLR TX (Transmitter)

Spark LINK XLR RX (Receiver)

USB C to C Cable (1.5 meters)

Quick Start Guide

Safety Instructions

PHYSICAL UNIT

DIMENSIONS

Spark LINK XLR TX:

L x H x W: 98.99mm x 27.6mm x 25.4mm (3.9in x 1.1in x 1in)

Spark LINK XLR RX:

L x H x W: 93.96mm x 27.6mm x 25.4mm (3.7in x 1.1in x 1in)

WEIGHT

Spark LINK XLR TX: 55.9 g (0.12lbs)

Spark LINK XLR RX: 50.7 g (0.11lbs)