

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it



Technical Datasheet

tasker® C801- 2x0,22 mm² - Double Sheathed Extra Flex Digital Audio 110 Ohm Cable AES/EBU



A	B	C	D	E
---	---	---	---	---

CATEGORY Digital Audio Cable (See Audio Catalogue)
APPLICATIONS Digital Audio Applications and DMX

- A:** First Black soft PVC sheath. Outer cable Diam. Ø 6,20 (±0,10) mm.
- B:** Second soft PVC sheath – Diam. Ø 4,40 (±0,10) mm.
- C:** Shielding O.F.C. Red Copper Spiral covering 100%
+ O.F.C. tinned copper Drain Wire.
- D:** Core Insulation with PPE, colored one Red and one Blue.
The conductors are wrapped together with waste textile filler.
Diam. Ø 1,50 mm (±0,10) mm.
- E:** O.F.C. tinned copper formation 28x0,10 mm.
Nom. Cross section 2x0,22 mm²

MARKING tasker® C 801 1x2x24 AWG AES/EBU 110 Ω DIGITAL DOUBLE JACKET AUDIO CABLE

CUSTOM PRODUCTION This product may be custom produced also in L.S.Z.H. polymer, PE, PUR, with or without Metallic Armor.

Cable Properties

Conductor Resistance	79,15 Ω/Km
Capacity Core/Core	50 pF/mt
Capacity Core/Shield	95 pF/mt
Impedance	110 Ω
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			